

Pr. ř. č. 1 km 0,000

577,00

577,91

577,92

500

[illegible]

Pr. ř. č. 5 km 0,080

576,98 576,98 576,98 576,98 577,89 579,44 579,44 579,66 579,65

1510 500 50 1850 150 500 500

579,85 579,86 579,83 2,0% 579,79 579,67 579,66 579,65

890

Vnější hrana
okružní

577,00

The drawing shows a road profile with a 2.0% grade. Key elevation points are marked: 579.70, 580.34, 580.38, 580.32, 580.26, 580.16, 580.15, and 580.13. Horizontal distances between points are 1120, 500, 50, 1850, 150, 495, and 500. A vertical curve is indicated with a 730m length and a 577.90 elevation. The road crosses the 'Vnější hrana country' boundary.

Distance (m)	Elevation (m)
0	579.70
1120	580.34
1620	580.38
1670	580.32
2270	580.26
2420	580.16
2570	580.15
2620	580.13

578,00	579,70	579,60	579,57	579,58	577,90	580,03	580,06	580,15	580,13
--------	--------	--------	--------	--------	--------	--------	--------	--------	--------

The drawing shows a road profile with the following data points and dimensions:

Stationing / Distance	Left Side Elevation	Right Side Elevation
Start (Left)	579.00	579.93
50m	579.52	581.06
100m	580.59	581.04
150m	580.41	581.00
200m	580.67	580.85
250m	580.85	580.82

Horizontal dimensions: 2030, 500, 50, 1850, 150, 500, 500.
 Vertical dimensions: 2.0% slope, 720 (at 150m stationing).
 Labels: "Vozňákova ulička" (Vozňákova street), "duby" (oaks).

[illegible]

580,00
 581,02
 581,90
 581,87
 579,75
 581,83
 581,82
 581,77
 581,75
 150 500 50 1850 150 700 500
 582,78 582,88 582,92 582,98 582,82 582,70 582,68 582,67
 2,0%
 240
 Dynamická
 únosnost

Př. ř. č. 9 km 0,160

582.76
582.72
582.52
582.59
581.95
582.22
582.30
582.70
582.68
582.67

150 500 50 1850 150 700 500

2.0%

582.76
582.88
583.02
582.88

582.76
582.82
582.70
582.68
582.67

240
582.30 výhledová úroveň

Př. ř. č. 10 km 0,180

Technical drawing of a road cross-section. The drawing shows a road profile with a 2.0% slope. Key elevations and dimensions are labeled:

- Top left elevation: 582.00
- Top right elevations: 583.81, 583.79, 583.71, 583.70, 583.66, 583.68
- Left side elevations: 585.09, 584.98, 584.82
- Right side elevations: 584.78, 584.65, 584.66, 584.67
- Horizontal dimensions: 150, 250, 500
- Vertical dimension: 1220
- Text labels: "Vjezdní trasa" (Approach route), "okružní" (roundabout), "okružní" (roundabout)

[illegible][illegible][illegible]

584.00		585.81		585.77		583.30		585.65		585.64		585.61		585.60
						585.71				the				
										and				

[illegible]

Technical drawing of a road profile. The vertical axis represents elevation in meters (m) and the horizontal axis represents distance in kilometers (km). The profile shows a road with a 2.0% downward slope. Key elevation points are marked: 585.00 at the start, 586.65 at the end of the profile, and intermediate points at 586.20, 586.19, 586.89, 586.19, 586.20, 586.32, 586.95, and 586.54. Horizontal distances between points are 950, 50, 1850, 150, 1000, and 500. A vertical curve is shown with a 1190m length and a 2.0% slope. The curve starts at a 587.74m elevation and ends at a 587.54m elevation. The curve is labeled 'Kvalitativní hodnocení' and 'Kvalitativní hodnocení'.

Technical drawing of a road cross-section. The drawing shows a road profile with a 2.0% slope. Key elevation points are marked: 589.62, 589.60, 589.58, 589.56, 589.54, 589.52, 589.50, 589.48, 589.46, 589.44, 589.42, 589.40, 589.38, 589.36, 589.34, 589.32, 589.30, 589.28, 589.26, 589.24, 589.22, 589.20, 589.18, 589.16, 589.14, 589.12, 589.10, 589.08, 589.06, 589.04, 589.02, 589.00, 588.98, 588.96, 588.94, 588.92, 588.90, 588.88, 588.86, 588.84, 588.82, 588.80, 588.78, 588.76, 588.74, 588.72, 588.70, 588.68, 588.66, 588.64, 588.62, 588.60, 588.58, 588.56, 588.54, 588.52, 588.50, 588.48, 588.46, 588.44, 588.42, 588.40, 588.38, 588.36, 588.34, 588.32, 588.30, 588.28, 588.26, 588.24, 588.22, 588.20, 588.18, 588.16, 588.14, 588.12, 588.10, 588.08, 588.06, 588.04, 588.02, 588.00, 587.98, 587.96, 587.94, 587.92, 587.90, 587.88, 587.86, 587.84, 587.82, 587.80, 587.78, 587.76, 587.74, 587.72, 587.70, 587.68, 587.66, 587.64, 587.62, 587.60, 587.58, 587.56, 587.54, 587.52, 587.50, 587.48, 587.46, 587.44, 587.42, 587.40, 587.38, 587.36, 587.34, 587.32, 587.30, 587.28, 587.26, 587.24, 587.22, 587.20, 587.18, 587.16, 587.14, 587.12, 587.10, 587.08, 587.06, 587.04, 587.02, 587.00, 586.98, 586.96, 586.94, 586.92, 586.90, 586.88, 586.86, 586.84, 586.82, 586.80, 586.78, 586.76, 586.74, 586.72, 586.70, 586.68, 586.66, 586.64, 586.62, 586.60, 586.58, 586.56, 586.54, 586.52, 586.50, 586.48, 586.46, 586.44, 586.42, 586.40, 586.38, 586.36, 586.34, 586.32, 586.30, 586.28, 586.26, 586.24, 586.22, 586.20, 586.18, 586.16, 586.14, 586.12, 586.10, 586.08, 586.06, 586.04, 586.02, 586.00, 585.98, 585.96, 585.94, 585.92, 585.90, 585.88, 585.86, 585.84, 585.82, 585.80, 585.78, 585.76, 585.74, 585.72, 585.70, 585.68, 585.66, 585.64, 585.62, 585.60, 585.58, 585.56, 585.54, 585.52, 585.50, 585.48, 585.46, 585.44, 585.42, 585.40, 585.38, 585.36, 585.34, 585.32, 585.30, 585.28, 585.26, 585.24, 585.22, 585.20, 585.18, 585.16, 585.14, 585.12, 585.10, 585.08, 585.06, 585.04, 585.02, 585.00, 584.98, 584.96, 584.94, 584.92, 584.90, 584.88, 584.86, 584.84, 584.82, 584.80, 584.78, 584.76, 584.74, 584.72, 584.70, 584.68, 584.66, 584.64, 584.62, 584.60, 584.58, 584.56, 584.54, 584.52, 584.50, 584.48, 584.46, 584.44, 584.42, 584.40, 584.38, 584.36, 584.34, 584.32, 584.30, 584.28, 584.26, 584.24, 584.22, 584.20, 584.18, 584.16, 584.14, 584.12, 584.10, 584.08, 584.06, 584.04, 584.02, 584.00, 583.98, 583.96, 583.94, 583.92, 583.90, 583.88, 583.86, 583.84, 583.82, 583.80, 583.78, 583.76, 583.74, 583.72, 583.70, 583.68, 583.66, 583.64, 583.62, 583.60, 583.58, 583.56, 583.54, 583.52, 583.50, 583.48, 583.46, 583.44, 583.42, 583.40, 583.38, 583.36, 583.34, 583.32, 583.30, 583.28, 583.26, 583.24, 583.22, 583.20, 583.18, 583.16, 583.14, 583.12, 583.10, 583.08, 583.06, 583.04, 583.02, 583.00, 582.98, 582.96, 582.94, 582.92, 582.90, 582.88, 582.86, 582.84, 582.82, 582.80, 582.78, 582.76, 582.74, 582.72, 582.70, 582.68, 582.66, 582.64, 582.62, 582.60, 582.58, 582.56, 582.54, 582.52, 582.50, 582.48, 582.46, 582.44, 582.42, 582.40, 582.38, 582.36, 582.34, 582.32, 582.30, 582.28, 582.26, 582.24, 582.22, 582.20, 582.18, 582.16, 582.14, 582.12, 582.10, 582.08, 582.06, 582.04, 582.02, 582.00, 581.98, 581.96, 581.94, 581.92, 581.90, 581.88, 581.86, 581.84, 581.82, 581.80, 581.78, 581.76, 581.74, 581.72, 581.70, 581.68, 581.66, 581.64, 581.62, 581.60, 581.58, 581.56, 581.54, 581.52, 581.50, 581.48, 581.46, 581.44, 581.42, 581.40, 581.38, 581.36, 581.34, 581.32, 581.30, 581.28, 581.26, 581.24, 581.22, 581.20, 581.18, 581.16, 581.14, 581.12, 581.10, 581.08, 581.06, 581.04, 581.02, 581.00, 580.98, 580.96, 580.94, 580.92, 580.90, 580.88, 580.86, 580.84, 580.82, 580.80, 580.78, 580.76, 580.74, 580.72, 580.70, 580.68, 580.66, 580.64, 580.62, 580.60, 580.58, 580.56, 580.54, 580.52, 580.50, 580.48, 580.46, 580.44, 580.42, 580.40, 580.38, 580.36, 580.34, 580.32, 580.30, 580.28, 580.26, 580.24, 580.22, 580.20, 580.18, 580.16, 580.14, 580.12, 580.10, 580.08, 580.06, 580.04, 580.02, 580.00, 579.98, 579.96, 579.94, 579.92, 579.90, 579.88, 579.86, 579.84, 579.82, 579.80, 579.78, 579.76, 579.74, 579.72, 579.70, 579.68, 579.66, 579.64, 579.62, 579.60, 579.58, 579.56, 579.54,

[illegible][illegible]

Technical drawing of a road cross-section. The drawing shows a road profile with a 2.0% slope. Key elevation points are marked: 589.00, 590.67, 590.04, 590.01, 590.02, 590.63, 590.51, 590.55, 590.65, 590.64. Horizontal dimensions are 615, 500, 50, 1850, 150, 560. Vertical dimensions are 591.37, 591.72, 591.76, 591.70, 591.66, 591.54, 591.53, 591.52. A dashed line indicates the 'Výšlet hrana cesty' (road edge line). A dimension of 830 is shown for the road width.

Př. ř. č. 17 km 0,340

Diagram illustrating a road cross-section profile with elevations and dimensions:

- Elevations (m):** 591.37, 591.37, 591.38, 591.40, 591.51, 591.51, 591.52.
- Dimensions (m):** 615, 500, 50, 1850, 150, 560.
- Slopes:** 2.0%.
- Labels:** Vnější hrana chodby (Outer edge of sidewalk).

[illegible][illegible]

Technical drawing of a road cross-section. The drawing shows a road profile with a 2.0% slope. Key elevation points are marked: 592.98, 592.21, 592.25, 593.01, 593.15, 593.05, 593.01, and 593.00. Horizontal dimensions are given as 390, 500, 50, 1850, 150, 530, and 500. A vertical dimension of 600 is also indicated. The drawing is labeled 'Př. ř. č. 19 km 0,380'.



[illegible]

Technical drawing of a road cross-section. The drawing shows a road profile with a 2.0% slope. Key elevation points are marked: 592.00 (road surface), 593.29, 593.55, 593.59, 593.62, 593.64, 593.66, 593.68, 593.69, 593.72, 593.75, 593.76, 593.77, 593.78, 593.79, 593.80, 593.81, 593.82, 593.83, 593.84, 593.85, 593.86, 593.87, 593.88, 593.89, 593.90, 593.91, 593.92, 593.93, 593.94, 593.95, 593.96, 593.97, 593.98, 593.99, 594.00, 594.01, 594.02, 594.03, 594.04, 594.05, 594.06, 594.07, 594.08, 594.09, 594.10, 594.11, 594.12, 594.13, 594.14, 594.15, 594.16, 594.17, 594.18, 594.19, 594.20, 594.21, 594.22, 594.23, 594.24, 594.25, 594.26, 594.27, 594.28, 594.29, 594.30, 594.31, 594.32, 594.33, 594.34, 594.35, 594.36, 594.37, 594.38, 594.39, 594.40, 594.41, 594.42, 594.43, 594.44, 594.45, 594.46, 594.47, 594.48, 594.49, 594.50, 594.51, 594.52, 594.53, 594.54, 594.55, 594.56, 594.57, 594.58, 594.59, 594.60, 594.61, 594.62, 594.63, 594.64, 594.65, 594.66, 594.67, 594.68, 594.69, 594.70, 594.71, 594.72, 594.73, 594.74, 594.75, 594.76, 594.77, 594.78, 594.79, 594.80, 594.81, 594.82, 594.83, 594.84, 594.85, 594.86, 594.87, 594.88, 594.89, 594.90, 594.91, 594.92, 594.93, 594.94, 594.95, 594.96, 594.97, 594.98, 594.99, 595.00. The drawing also shows a 2.0% slope and a 750m distance. The drawing is labeled 'Př. ř. č. 20 km 0,400'.

Technical drawing of a road cross-section. The drawing shows a road profile with a 2.0% slope. Key elevation points are marked: 592.00, 593.29, 593.21, 593.08, 593.04, 592.82, 591.72, 593.06, 593.13, 593.36, and 593.36. Horizontal distances are indicated: 655, 500, 50, 1850, 150, 250, and 500. A vertical curve is shown with a 2.0% slope. The road is labeled 'Vojštinova ulice' and 'dálnice'.

Technical drawing of a road cross-section. The drawing shows a road profile with a 2.0% slope. Key elevation points are marked: 593.06, 594.04, 594.08, 594.02, 593.98, 593.66, 593.06, and 593.85. Horizontal dimensions are given as 655, 500, 50, 1850, 150, 250, and 500. A dashed line indicates the 'výhledová hranice' (visibility limit). The drawing is labeled 'Př. ř. č. 21 km 0,440'.

592.00	592.06	593.67	592.70	593.14	593.81	593.82	592.06	593.85
--------	--------	--------	--------	--------	--------	--------	--------	--------

		Dokumentace pro vydání společného povolení a provádění stavby	
Souřadnicový systém: JTSK Výškový systém: BpV (PB=xxx) Projektant si vyhrazuje právo upravit, případně pozměňovat projekt na základě nových poznatků zjištěných během provádění stavby.			
Vypisoval: Ing. Bezdišek L.	Zodp. projekční Suchánek J.D., DiS.	Tech. kontrola	 prostav s.r.o. Na Kopce 316, 530 01 Mladá Boleslav IČ: 288 19 190, DIČ: CZ 288 19 180 Tel: 776 855 501, beseda@prostav.cz, www.bs.cz
Průcha T, DiS.		formát 3x44	
Investor Město Hlinsko, Poděbradovo náměstí 1, 539 01 Hlinsko		datum 05/2020	
Akce	účel DÚR+DSP + DPS		
CHODNÍK HLINSKO – RVÁČOV, ETAPA I k.ú. Hlinsko v Čechách, Vitanov		ž. zakázky	
		ž. kopie	
		archivní č.	
Obsah výkresu	Charakteristické příčné řezy	Měřítko 1:50	Č. výkresu D.4

Souřadnicový systém: JTSK
Výškový systém: BpV (PB=xxx)
Projektant si vyhrazuje právo doplňovat, případně pozměňovat
projekt na základě nových poznatků zjištěných během provádění stavby.

Investor	formát	3xA4
Město Hlinsko, Poděbradovo náměstí 1, 539 01 Hlinsko	datum	05/2020

k.ú. Hlinsko v Čechách, Vítanov	č. kopie
	archivní č.

Obsah výkresu	Charakteristické příčné řezy	Měřítko 1:50	Č. výkresu D.4
---------------	------------------------------	-----------------	-------------------